

ABS 12-24BRD



DUAL-VOLT ABS

ABS 12V ... 24V to 24V,

In: male bayonet, out: female bayonet



Special converter for the supply of a 24V anti lock system ABS/EBS out of 12V or 24V. The converter is equipped with ABS/EBS bayonet connectors. For inserting into the trailer cable. Male input / female output (Reverse configuration). The contacts 6 and 7 ("CAN-Bus") are connected through. Attention! The can bus lines require a separate level shifter. Without a level shifter the brake operates correctly on the ABS level.

- * **very fast done and water protected mounting without additional measures**
- * **simply insert into the ABS/EBS cable at the bayonet connection (Reverse configuration)**
- * **input voltage 12V and 24V**
- * **high power for additional functions like EBS and level control**
- * **the function of the info module remains active**
- * **electronical protection against reverse polarity without short circuit**
- * **protection against overload**
- * **reverse voltage proof independent from polarity**
- * **compact size by high efficiency**

input voltage:

9 ... 33V DC both lines

output voltage:

27V +5% (27 ... 32V if input above 27V)

output current line (term. 15):

0 ... 500mA

output current line (term. 30):

0 ... 10A (15A /20% on time cycle)

input connection:

Bayonet male connector, 7 pins automotive standard

output connection:

Bayonet female connector with lock shell, 7 pins automotive standard

cable length input:

app. 330mm

cable length output:

app. 330mm

dimensions:

200 x 70 x 40mm without cable outlet

mechanical protection:

IP 6K9K (entirely sealed)

total efficiency:

app. 80%

mass:

app. 1,20 kg

approval:

E1 10R-047161

Order Info:

11186