

ABS 12-24DTM



DUAL-VOLT ABS

ABS 12V ... 24V auf 24V

in rack, trailer side, 2 sockets



Special converter for the supply of a 24V anti lock system ABS/EBS out of 12V or 24V. The converter input is equipped with a 12V ABS/EBS socket and the output with a 24V ABS/EBS socket. The converter is mounted in a stainless steel rack and is ready for use. Preferential for trailer side mounting. Connection with the truck by the use of a 12V plug-plug-cable. The 24V trailer plug will be plugged in the converter. The contacts 6 and 7 ("CAN-Bus") are unequipped.

- * **input voltage 12V and 24V**
- * **high power for additional functions like EBS and level control**
- * **compact size by high efficiency**
- * **unit ready for use, fast to mount on the (drawbar) trailer**
- * **info-module works properly**
- * **electronical protection against reverse polarity without short circuit**
- * **protection against overload**
- * **stainless steel metal rack**
- * **reverse voltage proof independent from polarity**
- * **Up to 40km/h the cable KN-ABSFT for the input is also legal (follow regulations)**

input voltage:

9 ... 33V DC both lines

output voltage:

27V +5% (27 ... 32V if input above 27V)

output current line (term. 15):

0 ... 500mA

output current line (term. 30):

0 ... 10A (15A /20% on time cycle)

input connection:

ABS / EBS socket 12V
ISO'7638-2

output connection:

ABS / EBS socket 24V
ISO'7638-1

dimensions:

300 x 150 x 87mm + socket
45mm

mechanical protection:

entirely sealed (IP69K) and
stainless steel

total efficiency:

app. 80%

mass:

app. 3300g

Order Info:

ABS 12-24DTM