

TCU-FT

Trailer converter unit
12V to 24V for lights and ABS



Complete Trailer unit for farming tractors 12V to 24V for lights and ABS. At the input are plugs and at the outlet are sockets. Park sockets are available when the converter is not in use to take the free plugs. The unit is mounted in a stainless steel metal rack. The converters inside are ABS 12-24 and ASV 12-24-6H.

- * Includes all components for "plug and go"
- * Input 1 with a 7-contact plug for the lights
- * Input 2 with a ABS/EBS standard plug, 5 contacts connected
- * Output 1 with a 7 contact 24V "7N" socket and a 15 contact 24V lights socket
- * Output 2 with a 7 contact 24V ABS/EBS socket, 5 contacts connected
- * Park sockets for both plugs when not in use
- * Stainless steel metal rack is removable without detaching the screws

Input voltage:	12V nominal
Output voltage:	24V nominal
Output power 1:	Lamps/LEDs: 6 x130W, maximum 500W nominal
Output power 2:	ABS/EBS maximum 2 units
Connection input 1:	Lights, Plug 12V 7 contacts ISO1724
Connection input 2:	ABS, Plug 12V 5 contacts ISO7638-2
Connection output 1:	Lights, Socket 24V 7 contacts ISO1185 15 contacts ISO12098
Connection output 2:	ABS/EBS, 24V Socket 5 contacts ISO7638-1
Cable length input:	Input1 / Input 2: about 700mm each
Mechanical protection:	Each component is entirely sealed (IP69K)
Dimensions:	412 x 196 x 100mm Metal body sockets excluded
Mass:	6,4 kg

Order Info:

TCU-FT