

W 24-12-10P

SEMI-VOLT 10 Plus
24V to 12V 10(15)A, two lines



High-end voltage converter with medium power for 12V devices at 24V car line. For the simultaneous supply of permanent plus and ignition plus.

- * provides permanent plus (term. 30) and ignition plus (term. 15) up to the maximum load
- * concept of high development standard:
 - real voltage division, discharge protection of 12V device is effective
 - significant low self current consumption of 0,7 mA
 - very high efficiency of about 94%
- * overload capacity up to 15A for about 5 min.
- * small dimensions
- * compact plug (AMP Mate Lock)
- * 5kW-peak-safety-diode to prevent overvoltage from car line

input voltage:	16 ... 30V DC
switch line:	ignition plus (term 15) connects second output
output voltage:	8 ... 15V DC input voltage gets halved
output current:	10A permanent, 15A for about 5 min.
dimensions:	129 x 70 x 25mm incl. Plug
connection:	5-poles connector, round contacts (AMP Mate Lock)
temperature range:	-40 ... +75°C, derating T>45°C
electrical protection:	overcurrent, overtemperature, input transients
mechanical protection:	entirely sealed
current without load:	0,7mA at 24V
efficiency:	about 94%
mass:	about 385g

Order Info:

W 24-12-10P