

W 24-12-26P

SEMI-VOLT 26 Plus
24V to 12V 26(35)A, two lines



High-end voltage converter of higher power for 12V consumers at 24V car line. For the simultaneous supply of permanent plus and ignition plus

- * provides permanent plus (term. 30) and ignition plus (term. 15) up to the maximum load
- * concept of high development standard:
 - real voltage division, discharge protection of 12V device is effective
 - significant low self current consumption of 0,7mA
 - very high efficiency of about 94%
- * overload capacity up to 35A for about 5 min.
- * small dimensions
- * high-power-plug of high quality
- * 5kW-peak-safety-diode to prevent overvoltage from car line

input voltage :	16 ... 30V DC
output voltage:	8 ... 15V DC input voltage gets halved
output current:	26A permanent, 35A for about 5 min.
current without load:	0,7mA at 24V
connections:	5-pole plug "Anderson Powerpole Modular"
dimensions:	200 x 70 x 40mm
mechanical protection:	IP 6K9K (entirely sealed)
electrical protection:	overcurrent, overtemperature, input transients
switching line:	ignition plus (term. 15) switches 2nd outlet
temperature range:	-40 ... +75°C, derating T>45°C
efficiency:	app. 92%
mass:	app. 0,90 kg
approval:	CE

Order Info:

10080